



Tachometer



Fluke 931

Fluke 930 Non-contact Tachometer Fluke 931 Contact and Non-contact Dual-purpose Tachometer

The Fluke 931 is a handheld tachometer, which integrates the contact and non-contact speed measurement functions and can accurately measure the revolutions per minute (RPM) or surface speed on rotating machinery. Where equipment needs quick troubleshooting to diagnose problems, the Fluke 930 or 931 is the right tool for the job. The Fluke 930 is equivalent to a Fluke 931 with the ability to measure via stroboscope in non-contact mode only, at the same accuracy and for a lower price. With the ability for contact measurement and non-contact combined, the Fluke 931 provides greater flexibility for the professional technician.

Product highlights

- 6-digit backlit display for easy data visualization
- Signal detection reminder minimizes false readings
- Maximum/Minimum/Average value and final readings
- Small size with rugged housing over mold to protect against drops
- Easy switching of the contact and non-contact measurement modes (Fluke 931 only)
- Different speed measuring heads to adapt to different measurement occasions (Fluke 931 only)
- 1 year warranty



Applications

- Heavy manufacturing environments, e.g. automotive, textile, pulp and paper, metalwork
- Water purification plants
- HVAC compressors for industrial systems

Fluke 930 and 931 Main technical parameters

Rotation speed measurement	
Range	Optical (non-contact) measurement: 1 to 99999 revolutions/minute Contact measurement: 1 to 19999 revolutions/minute (Fluke 931 only)
Precision	±0.02 % RD+1
Sensing distance	(optical) 500 mm
Specifications	
Battery type	(2) 1.5V LR6 (alkaline) AA battery
Battery life	About 40 hours
Operating temperature	0 °C to 50 °C
Storage temperature	-20 °C to 70 °C
Weight	250 g
Dimensions	175 × 60 × 28 mm
Warranty period	1 year



CONTACT DETAIL



tasira@rediffmail.com



2522 8205, 2523 1145



#293, (Old 142)
Linghi Chetty Street,
Chennai-600 001



www.tasirainstrumentations.com